



### Built to last

Sturdy industrial-strength designed for continuous high-traffic operation.



### Stay Connected

With two SIM slots and an eSIM, the MAX Adapter always has a way to connect.

### Instant Unbreakable VPN

Compatible with SpeedFusion Cloud, enabling an unbreakable VPN to be built to any SpeedFusion-enabled device.

### Compatible with 5G

MAX Adapter now offers a 5G compatible device option. Bringing 5G connectivity to your devices.

**MAX ADAPTER**  
State-of-the-art Cellular Modem at a breakthrough price point



### Portable

The light and sleek enclosure offers portability in the palm of your hands.



Connect with



## Peplink Products

Protect and reinforce products<sup>^</sup> with a USB port and make it a 5G/LTE WAN.

 [Learn More](#)

OR

## Windows & Linux\* Devices

Providing 5G/LTE connectivity for  
Windows and Linux devices on-the-go.



<sup>^</sup> For compatible models, please refer to the MAX Adapter [FAQ](#).

\* For users on the Linux, please refer to our MAX Adapter user manual to set up.



## Specifications

<b>Cellular WAN Interfaces</b>	Single 5G Modem	<b>Weight</b>	120g
<b>Redundant SIM Slot</b>	Yes	<b>Operating Temperature</b>	32° – 104°F / 0° – 40°C
<b>Downlink/Uplink Datarate</b>	5G: 4 Gbps / 700 Mbps LTE CAT-20: 2 Gbps / 150 Mbps	<b>Humidity</b>	15% – 95% (non-condensing)
<b>Antenna Connectors</b>	4x SMA Cellular	<b>Warranty</b>	1-Year Limited Warranty
<b>Power Input</b>	5V USB-C	<b>Certifications</b>	FCC, CE, IC
<b>Power Consumption</b>	5W (nominal), 8W (max.)	<b>Package Content</b>	MAX Adapter 5G, 4x LTE/5G LTE Antennas (ACW-235), USB-C Female to USB-A Male Adapter, USB-C Power Cable
<b>Dimensions</b>	3.9 x 2.8 x 0.6 inches / 100 x 71 x 15 mm		

## Ordering information

Product Code	Carrier / Category	5G Bands	LTE Bands
MAX-ADP-5GH-T	Global / 5G	<b>5G (NSA) Sub 6Ghz:</b> n1, n2, n3, n5, n28, n41, n66, n71, n77, n78, n79  <b>5G (SA) Sub 6Ghz:</b> n77, n78, n79	B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B32, B34, B38, B39, B40, B41, B42, B46, B48, B66, B71



## Specifications

<b>Cellular WAN Interfaces</b>	Single LTE Modem	<b>Weight</b>	120g
<b>Redundant SIM Slot</b>	Yes	<b>Operating Temperature</b>	32° – 104°F / 0° – 40°C
<b>Downlink/Uplink Datarate</b>	CAT-12: 600 Mbps / 150 Mbps CAT-6: 300Mbps / 50Mbps	<b>Humidity</b>	15% – 95% (non-condensing)
<b>Antenna Connectors</b>	2x SMA Cellular, 1x SMA GPS	<b>Warranty</b>	1-Year Limited Warranty
<b>Power Input</b>	5V USB-C	<b>Certifications</b>	FCC, CE, IC
<b>Power Consumption</b>	5W (nominal), 8W (max.)	<b>Package Content</b>	MAX Adapter, 2x LTE Antennas (ACW-813), USB-C Female to USB-A Male Adapter, USB-C Power Cable
<b>Dimensions</b>	3.9 x 2.8 x 0.6 inches / 100 x 71 x 15 mm	<b>US Carrier Certifications</b>	Verizon, AT&T

## Ordering information

Product Code	Carrier / Category	LTE Bands	3G Bands
MAX-ADP-LTEA-K-T	Global CAT-12	B1, B2, B3, B4, B5, B7, B8, B9, B12, B13, B18, B19, B20, B26, B28, B29, B30, B32, B41, B42, B43, B46, B48, B66	HSPA+: B1, B2, B4, B5, B6, B8, B9, B19
MAX-ADP-LTEA-R-T	America CAT-12	B1, B2, B3, B4, B5, B7, B8, B9, B12, B13, B14, B18, B19, B20, B26, B29, B30, B32, B41, B42, B43, B46, B48, B66	HSPA+: B1, B2, B4, B5, B6, B8, B9, B19
MAX-ADP-LTEA-W-T	Global CAT-6	B1, B2, B3, B4, B5, B7, B8, B12, B13, B20, B25, B26, B29, B30, B41	WCDMA/HSPA+/DC-HSPA+: B1, B2, B3, B4, B5, B8

## Accessories

Product Code	Description
ACW-232	GPS Antenna